

# SAFETY DATA SHEET

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT

**Product Name:** PAVING ASPHALT PG 64-22  
**Product Description:** Asphalt/Bitumen  
**Product Code:** 1010902025A5, 16515, 8404  
**Intended Use:** Mainly used for road paving, Miscellaneous industrial applications

### COMPANY IDENTIFICATION

**Supplier:** Canada Imperial Oil Limited, An Affiliate of Exxon Mobil Corporation  
P.O. Box 2480, Station M  
Calgary, ALBERTA T2P 3M9 Canada  
**24 Hour Health Emergency** 1-866-232-9563  
**Transportation Emergency Phone** 1-866-232-9563  
**Supplier General Contact** 1-800-567-3776

## SECTION 2 HAZARDS IDENTIFICATION

This material is not hazardous according to regulatory guidelines (see (M)SDS Section 15).

### Other hazard information:

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 29 CFR 1910.1200.

### PHYSICAL / CHEMICAL HAZARDS

Thermal burn hazard - contact with hot material may cause thermal burns.

### HEALTH HAZARDS

Exposure to high fume concentrations from heated asphalt may cause eye and respiratory tract irritation. Hydrogen sulfide, a highly toxic gas, may be present. Signs and symptoms of overexposure to hydrogen sulfide include respiratory and eye irritation, dizziness, nausea, coughing, a sensation of dryness and pain in the nose, and loss of consciousness. Odor does not provide a reliable indicator of the presence of hazardous levels in the atmosphere.

### ENVIRONMENTAL HAZARDS

No significant hazards.

<b>NFPA Hazard ID:</b>	Health: 2	Flammability: 1	Reactivity: 0
<b>HMIS Hazard ID:</b>	Health: 1	Flammability: 1	Reactivity: 0

Product Name: PAVING ASPHALT PG 64-22  
Revision Date: 29 Jul 2019  
Page 2 of 11

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a complex substance.

#### Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
ASPHALT (PETROLEUM)	8052-42-4	100%	None

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

### SECTION 4 FIRST AID MEASURES

#### INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

#### SKIN CONTACT

Wash contact areas with soap and water. If burned by contact with hot material, molten material adhering to skin should be cooled as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.

#### EYE CONTACT

Flush thoroughly with water for at least 15 minutes. Get medical assistance.

#### INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

### SECTION 5 FIRE FIGHTING MEASURES

#### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use dry chemical, carbon dioxide (CO<sub>2</sub>), or a dry, noncombustible material such as, dry sand or earth, to extinguish flames.

**Inappropriate Extinguishing Media:** DO NOT USE WATER.

Product Name: PAVING ASPHALT PG 64-22

Revision Date: 29 Jul 2019

Page 3 of 11

## FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Hydrogen sulfide, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulfur oxides

## FLAMMABILITY PROPERTIES

**Flash Point [Method]:** 230°C (446°F) [ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: 0.5 UEL: 5.0

**Autoignition Temperature:** N/D

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

### PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H<sub>2</sub>S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Chemical goggles and face shield are recommended if contact of eyes with hot product or vapours is possible. Small spills: normal work clothes are usually adequate. Large spills: full body suit of chemical and thermal resistant material is recommended. Work gloves (preferably gauntlet style) that provide adequate chemical resistance. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. If contact with hot product is possible or anticipated, heat-resistant and thermally insulated gloves are recommended.

### SPILL MANAGEMENT

**Land Spill:** Stop leak if you can do it without risk. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

**Water Spill:** Stop leak if you can do it without risk. Material will sink. Consult an expert.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Product Name: PAVING ASPHALT PG 64-22  
 Revision Date: 29 Jul 2019  
 Page 4 of 11

## ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7 HANDLING AND STORAGE

### HANDLING

Avoid vapors from heated materials to prevent exposure to potentially toxic/irritating fumes. Hydrogen sulfide (H<sub>2</sub>S) may be given off when this material is heated. Do not depend on sense of smell for warning. When heating to normal handling temperatures, avoid local overheating. Use only with adequate ventilation. Prevent small spills and leakage to avoid slip hazard.

**Loading/Unloading Temperature:** > 90°C (194°F)

**Static Accumulator:** This material is not a static accumulator.

### STORAGE

Non-absorbent insulation such as foam glass is recommended for tankage and piping. Do not store in open or unlabelled containers.

**Storage Temperature:** < 190°C (374°F)

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard			NOTE	Source
ASPHALT (PETROLEUM) [benzene solubles]	Fume, inhalable	TWA	0.5 mg/m <sup>3</sup>		N/A	ACGIH
Asphalt fumes [benzene solubles]	Fume, inhalable	TWA	0.5 mg/m <sup>3</sup>		N/A	ACGIH
Hydrogen sulfide		Ceiling	20 ppm		N/A	OSHA Z2
Hydrogen sulfide		Maximum concentration	50 ppm		N/A	OSHA Z2
Hydrogen sulfide		STEL	14 mg/m <sup>3</sup>	10 ppm	N/A	ExxonMobil
Hydrogen sulfide		TWA	7 mg/m <sup>3</sup>	5 ppm	N/A	ExxonMobil
Hydrogen sulfide		STEL	5 ppm		N/A	ACGIH
Hydrogen sulfide		TWA	1 ppm		N/A	ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

### ENGINEERING CONTROLS

Product Name: PAVING ASPHALT PG 64-22

Revision Date: 29 Jul 2019

Page 5 of 11

---

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

## PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Positive-pressure, air-supplied respirator in areas where H<sub>2</sub>S vapors may accumulate is recommended.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If product is hot, thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

**Eye Protection:** If contact with material may occur, safety glasses and face shield are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

If product is hot, thermally protective, chemical resistant apron and long sleeves are recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

<b>SECTION 9</b>
------------------

<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
---

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

Product Name: PAVING ASPHALT PG 64-22  
 Revision Date: 29 Jul 2019  
 Page 6 of 11

**Physical State:** Solid  
**Color:** Black  
**Odor:** Petroleum/Solvent  
**Odor Threshold:** N/D

**IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION**

**Relative Density (at 25 °C):** 1.032  
**Flammability (Solid, Gas):** N/A  
**Flash Point [Method]:** 230°C (446°F) [ASTM D-92]  
**Flammable Limits (Approximate volume % in air):** LEL: 0.5 UEL: 5.0  
**Autoignition Temperature:** N/D  
**Boiling Point / Range:** > 400°C (752°F)  
**Decomposition Temperature:** N/D  
**Vapor Density (Air = 1):** > 1 at 101 kPa  
**Vapor Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C  
**Evaporation Rate (n-butyl acetate = 1):** N/A  
**pH:** N/A  
**Log Pow (n-Octanol/Water Partition Coefficient):** > 6  
**Solubility in Water:** Negligible  
**Viscosity:** [N/A at 40 °C] | 350 cSt (350 mm<sup>2</sup>/sec) at 135°C  
**Oxidizing Properties:** See Hazards Identification Section.

**OTHER INFORMATION**

**Freezing Point:** N/A  
**Melting Point:** N/A

<b>SECTION 10</b>	<b>STABILITY AND REACTIVITY</b>
-------------------	---------------------------------

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Contact of hot product with water., Overheating.

**MATERIALS TO AVOID:** Alkalies, Halogens, Strong Acids, Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

<b>SECTION 11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-------------------	----------------------------------

**INFORMATION ON TOXICOLOGICAL EFFECTS**

<b>Hazard Class</b>	<b>Conclusion / Remarks</b>
<b>Inhalation</b>	
Acute Toxicity: (Rat) 4 hour(s) LC50 > MAXCONC	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
Irritation: No end point data for material.	Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.

Product Name: PAVING ASPHALT PG 64-22

Revision Date: 29 Jul 2019

Page 7 of 11

<b>Ingestion</b>	
Acute Toxicity (Rat): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401
<b>Skin</b>	
Acute Toxicity (Rabbit): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skin Corrosion/Irritation: Data available.	Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
<b>Eye</b>	
Serious Eye Damage/Irritation: Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
<b>Sensitization</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available.	Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
<b>Aspiration:</b> Data available.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
<b>Germ Cell Mutagenicity:</b> Data available.	Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 474
<b>Carcinogenicity:</b> Data available.	Not expected to cause cancer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451
<b>Reproductive Toxicity:</b> Data available.	Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 422
<b>Lactation:</b> No end point data for material.	Not expected to cause harm to breast-fed children.
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: Data available.	Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 410 412 413 422

## OTHER INFORMATION

### For the product itself:

Asphalt (bitumen): May contain low levels of polycyclic aromatic compounds (PACs), some of which are suspected of causing cancer under conditions of poor industrial hygiene and prolonged repeated contact. These PACs may also be inhaled. Inhalation studies at high concentrations of fumes resulted in bronchitis, pneumonitis, fibrosis and cell damage. Avoid contact with the asphalt emissions.

### Contains:

HYDROGEN SULFIDE : Chronic health effects due to repeated exposures to low levels of H<sub>2</sub>S have not been established. High level (700 ppm) acute exposure can result in sudden death. High concentrations will lead to cardiopulmonary arrest due to nervous system toxicity and pulmonary edema. Lower levels (150 ppm) may overwhelm sense of smell, eliminating warning of exposure. Symptoms of overexposure to H<sub>2</sub>S include headache, fatigue, insomnia, irritability, and gastrointestinal problems. Repeated exposures to approximately 25 ppm will irritate mucous membranes and the respiratory system and have been implicated in some eye damage.

Product Name: PAVING ASPHALT PG 64-22

Revision Date: 29 Jul 2019

Page 8 of 11

EMISSIONS (generated from heated bitumen product): According to The International Agency for Research on Cancer (IARC), certain specific occupational uses of bitumen products may result in carcinogenic hazards, as follows: (a) Occupational exposures to oxidized bitumens and their emissions during roofing are 'probably carcinogenic to humans' (Group 2A), (b) occupational exposures to hard bitumens and their emissions during mastic asphalt work are 'possibly carcinogenic to humans' (Group 2B), and (c) occupational exposures to straight-run bitumens and their emissions during road paving are 'possibly carcinogenic to humans' (Group 2B). These levels of hazard identified by IARC are associated with the specified occupational uses which require heating. Oxidized asphalts have been defined as having a Penetration Index (PI) of > 2.0.

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = NTP CARC

3 = IARC 1

5 = IARC 2B

2 = NTP SUS

4 = IARC 2A

6 = OSHA CARC

## SECTION 12

## ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

### MOBILITY

Majority of components -- Low water solubility, expected to sink and migrate into the sediment. Expected to partition to sediment and wastewater solids.

Material -- Low potential to migrate through soil.

### PERSISTENCE AND DEGRADABILITY

#### Biodegradation:

Material -- Expected to be persistent.

### BIOACCUMULATION POTENTIAL

Material -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

## SECTION 13

## DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.



## DISPOSAL RECOMMENDATIONS

Dispose of waste at an appropriate treatment & disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

## REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

## SECTION 14

## TRANSPORT INFORMATION

### LAND (DOT)

**Proper Shipping Name:** ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt)  
**Hazard Class & Division:** 9  
**ID Number:** 3257  
**Packing Group:** III  
**ERG Number:** 128  
**Label(s):** 9  
**Transport Document Name:** UN3257, ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt), 9, PG III

Footnote: Material is not regulated when shipped at temperatures below 212 F and its flash point.

**LAND (TDG):** Not Regulated for Land Transport

### SEA (IMDG)

**Proper Shipping Name:** ELEVATED TEMPERATURE LIQUID, N.O.S. (Bitumen)  
**Hazard Class & Division:** 9  
**EMS Number:** F-A,S-P  
**UN Number:** 3257  
**Packing Group:** III  
**Marine Pollutant:** No  
**Label(s):** 9 (ET)  
**Transport Document Name:** UN3257, ELEVATED TEMPERATURE LIQUID, N.O.S. (Bitumen), 9, PG III

### AIR (IATA)

**Proper Shipping Name:** NOT STANDARD PRACTICE  
**Hazard Class & Division:**

Product Name: PAVING ASPHALT PG 64-22  
 Revision Date: 29 Jul 2019  
 Page 10 of 11

**UN Number:**  
**Packing Group:** (N/A)  
**Label(s) / Mark(s):**  
**Transport Document Name:** NOT STANDARD PRACTICE,

[Footnote: Product classified as UN 3257 is forbidden by air transport but the product may be transported by air if its temperature is less than 100 deg. C (212 deg. F). If the product is offered for transport at less than 100 deg. C (212 deg. F), the transport classification is Not Regulated.]

<b>SECTION 15</b>	<b>REGULATORY INFORMATION</b>
-------------------	-------------------------------

**OSHA HAZARD COMMUNICATION STANDARD:** This material is not considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**Listed or exempt from listing/notification on the following chemical inventories:** AICS, DSL, ENCS, IECSC, KECI, PICCS, TSCA

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

**CERCLA:** This material is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.

**SARA (311/312) REPORTABLE GHS HAZARD CLASSES:** None.

**SARA (313) TOXIC RELEASE INVENTORY:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
ASPHALT (PETROLEUM)	8052-42-4	1, 13, 16, 17, 18

--REGULATORY LISTS SEARCHED--

- |               |                  |                   |             |
|---------------|------------------|-------------------|-------------|
| 1 = ACGIH ALL | 6 = TSCA 5a2     | 11 = CA P65 REPRO | 16 = MN RTK |
| 2 = ACGIH A1  | 7 = TSCA 5e      | 12 = CA RTK       | 17 = NJ RTK |
| 3 = ACGIH A2  | 8 = TSCA 6       | 13 = IL RTK       | 18 = PA RTK |
| 4 = OSHA Z    | 9 = TSCA 12b     | 14 = LA RTK       | 19 = RI RTK |
| 5 = TSCA 4    | 10 = CA P65 CARC | 15 = MI 293       |             |

Code key: CARC=Carcinogen; REPRO=Reproductive

<b>SECTION 16</b>	<b>OTHER INFORMATION</b>
-------------------	--------------------------

Product Name: PAVING ASPHALT PG 64-22  
Revision Date: 29 Jul 2019  
Page 11 of 11

---

N/D = Not determined, N/A = Not applicable

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

- Composition: Component Table information was modified.
- Section 08: Exposure Limits Table information was modified.
- Section 12: information was modified.
- Section 15: SARA (311/312) REPORTABLE GHS HAZARD CLASSES information was added.
- Section 15: SARA (311/312) REPORTABLE HAZARD CATEGORIES information was deleted.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

Internal Use Only  
MHC: 0B, 0B, 0, 0, 0, 1 PPEC: C  
DGN: 5014902 (1016145)

---

Copyright 2002 Exxon Mobil Corporation, All rights reserved