

---

## SAFETY DATA SHEET

|                  |   |
|------------------|---|
| <b>SECTION 1</b> | <b>PRODUCT AND COMPANY IDENTIFICATION</b> |
|------------------|---|

### PRODUCT

**Product Name:** MOBIL BRAKE FLUID DOT 4  
**Product Description:** Glycol Ether  
**Product Code:** 330936-84, 351010603010  
**Intended Use:** Brake fluid

### COMPANY IDENTIFICATION

**Supplier:** ExxonMobil Hong Kong Limited  
Suite 2301-02&06-08, 23/F, Central Plaza  
18 Harbour Road  
Wanchai Hong Kong

**24 Hour Emergency Telephone** 800-968-793 / +1-703-527-3887  
**Supplier General Contact** (852) 2172 8300

**Supplier:** BRENNTAG CHEMICALS (HK) PTE LTD  
6/F, Epoch Industrial Building,  
8 Cheung Ho Street,  
Tsing Yi, NT Hong Kong

**Supplier General Contact** (852) 3590 3909/(852)3590 6306

|                  |                               |
|------------------|-------------------------------|
| <b>SECTION 2</b> | <b>HAZARDS IDENTIFICATION</b> |
|------------------|-------------------------------|

This material is hazardous according to UN GHS Revision 4 Criteria. Classification includes all GHS hazard classes and all GHS hazard categories. For hazard categories with two cut-off/concentration limits, classification was based on the higher limit.

### CLASSIFICATION:

Eye irritation: Category 2A. Reproductive toxicant (developmental): Category 2.

### LABEL:

**Symbol:**

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 2 of 11



**Signal Word:** Warning

**Hazard Statements:**

Health: H319: Causes serious eye irritation. H361: Suspected of damaging the unborn child.

**Precautionary Statements:**

General: P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.

Prevention: P280: Wear protective gloves/protective clothing/eye protection/face protection. P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P264: Wash skin thoroughly after handling.

Response: P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313: IF exposed or concerned: Get medical advice/attention. P337 + P313: If eye irritation persists: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

**Other hazard information:**

**PHYSICAL / CHEMICAL HAZARDS**

No significant hazards.

**HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. Ingestion may cause serious adverse effects and may be fatal. May cause kidney failure and central nervous system effects. Prolonged exposure to elevated concentrations of mist or liquid may cause irritation of the skin, eyes, and respiratory tract.

**ENVIRONMENTAL HAZARDS**

No significant hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 3 of 11

|                  |   |
|------------------|---|
| <b>SECTION 3</b> | <b>COMPOSITION / INFORMATION ON INGREDIENTS</b> |
|------------------|---|

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

| Name   | CAS#       | Concentration* | GHS Hazard Codes |
|--|------------|----------------|------------------|
| 2-(2-METHOXYETHOXY)-ETHANOL                          | 111-77-3   | 1 < 3%         | H361(D)          |
| ETHANOL, 2,2-OXYBIS-                                 | 111-46-6   | 3 - < 5%       | H302             |
| ETHANOL, 2-(2-(2-BUTOXYETHOXY)ETHOXY)-               | 143-22-6   | 20 < 30%       | H318             |
| ETHANOL, 2-(2-BUTOXYETHOXY)-                         | 112-34-5   | 1 - < 3%       | H319(2A)         |
| POLY GLYCOL MONO BUTYL ETHER                         | 9004-77-7  | 5 - < 10%      | H318             |
| TRIS[2-[2-(2-METHOXYETHOXY)ETHOXY]ETHYL] ORTHOBORATE | 30989-05-0 | 20 - < 30%     | H361(D)          |

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

|                  |                           |
|------------------|---------------------------|
| <b>SECTION 4</b> | <b>FIRST AID MEASURES</b> |
|------------------|---------------------------|

**INHALATION**

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

**SKIN CONTACT**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**EYE CONTACT**

Flush thoroughly with water for at least 15 minutes. Get medical assistance.

**INGESTION**

Seek immediate medical attention. Do not induce vomiting.

**NOTE TO PHYSICIAN**

This product contains ethylene glycol and/or diethylene glycol which, if ingested, are metabolized to toxic metabolites by the enzyme alcohol dehydrogenase, for which ethanol and 4-methylpyrazole \{U.S. drug name Fomepizole, trade name Antizol\} are antagonists. Administration of oral or intravenous ethanol or intravenous 4-methylpyrazole may arrest further metabolism of this material and thereby ameliorate the toxicity. Use of ethanol or 4-methylpyrazole does not affect toxic metabolites that are already present and is not a substitute for hemodialysis.

---

|           |                        |
|-----------|------------------------|
| SECTION 5 | FIRE FIGHTING MEASURES |
|-----------|------------------------|

#### EXTINGUISHING MEDIA

**Appropriate Extinguishing Media:** Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight streams of water or standard foam

#### FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Incomplete combustion products, Oxides of carbon, Smoke, Fume

#### FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >143 C (290 F) [ ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Autoignition Temperature:** N/D

|           |                             |
|-----------|-----------------------------|
| SECTION 6 | ACCIDENTAL RELEASE MEASURES |
|-----------|-----------------------------|

#### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

#### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

#### SPILL MANAGEMENT

**Land Spill:** Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do so without risk. Warn other shipping. This product emulsifies, disperses or is miscible in water. Remove material, as much as possible, using

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 5 of 11

mechanical equipment.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

**ENVIRONMENTAL PRECAUTIONS**

Prevent entry into waterways, sewers, basements or confined areas.

|                  |                             |
|------------------|-----------------------------|
| <b>SECTION 7</b> | <b>HANDLING AND STORAGE</b> |
|------------------|-----------------------------|

**HANDLING**

Avoid all personal contact. Prevent small spills and leakage to avoid slip hazard.

**Static Accumulator:** This material is not a static accumulator.

**STORAGE**

Do not store in open or unlabelled containers.

|                  |  |
|------------------|--|
| <b>SECTION 8</b> | <b>EXPOSURE CONTROLS / PERSONAL PROTECTION</b> |
|------------------|--|

**EXPOSURE LIMIT VALUES**

Exposure limits/standards (Note: Exposure limits are not additive)

| Substance Name               | Form                          | Limit/Standard |          |  | Note | Source    | Year |
|------------------------------|-------------------------------|----------------|----------|--|------|-----------|------|
| ETHANOL, 2,2-OXYBIS-         |                               | TWA            | 10 mg/m3 |  |      | OARS WEEL | 2018 |
| ETHANOL, 2-(2-BUTOXYETHOXY)- | Inhalable fraction and vapour | TWA            | 10 ppm   |  |      | ACGIH     | 2020 |

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

**ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded.

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 6 of 11

---

## PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:  
No protection is ordinarily required under normal conditions of use and with adequate ventilation. Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:  
Chemical resistant gloves are recommended. Nitrile, Viton

**Eye Protection:** Chemical goggles are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:  
Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 7 of 11

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

Physical State: Liquid

Colour: Yellow-Orange

Odour: Characteristic

Odour Threshold: N/D

## IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 20 C): 1.04

Flash Point [Method]: >143 C (290 F) [ ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Flammability (Solid, Gas): N/A

Autoignition Temperature: N/D

Boiling Point / Range: > 260 C (500 F)

Vapour Density (Air = 1): N/D

Vapour Pressure: N/D

Evaporation Rate (n-butyl acetate = 1): N/D

pH: N/A

Log Pow (n-Octanol/Water Partition Coefficient): N/D

Solubility in Water: Complete

Viscosity: 6.5 cSt (6.5 mm<sup>2</sup>/sec) at 40 C | >2.1 cSt (2.1 mm<sup>2</sup>/sec) at 100 C [ASTM D341]

Freezing Point: N/D

Melting Point: N/A

Decomposition Temperature: N/D

Oxidizing Properties: See Hazards Identification Section.

## OTHER INFORMATION

### SECTION 10

### STABILITY AND REACTIVITY

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**MATERIALS TO AVOID:** Strong oxidisers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

### SECTION 11

### TOXICOLOGICAL INFORMATION

Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 8 of 11

---

**INFORMATION ON TOXICOLOGICAL EFFECTS**

| <b>Hazard Class</b>  | <b>Conclusion / Remarks</b>  |
|--|--|
| <b>Inhalation</b>  |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Irritation: No end point data for material.                    | Negligible hazard at ambient/normal handling temperatures.   |
| <b>Ingestion</b>   |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| <b>Skin</b>  |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Skin Corrosion/Irritation: No end point data for material.     | Negligible irritation to skin at ambient temperatures. Based on assessment of the components.                                      |
| <b>Eye</b>   |  |
| Serious Eye Damage/Irritation: No end point data for material. | Irritating and will injure eye tissue. Based on assessment of the components.  |
| <b>Sensitisation</b>   |  |
| Respiratory Sensitization: No end point data for material.     | Not expected to be a respiratory sensitizer.   |
| Skin Sensitization: No end point data for material.            | Not expected to be a skin sensitizer. Based on assessment of the components.   |
| <b>Aspiration:</b> No end point data for material.             | Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.                                     |
| <b>Germ Cell Mutagenicity:</b> No end point data for material. | Not expected to be a germ cell mutagen. Based on assessment of the components.   |
| <b>Carcinogenicity:</b> No end point data for material.        | Not expected to cause cancer. Based on assessment of the components.   |
| <b>Reproductive Toxicity:</b> No end point data for material.  | Caused damage to the fetus in laboratory animals, but the relevance to humans is uncertain. Based on assessment of the components. |
| <b>Lactation:</b> No end point data for material.              | Not expected to cause harm to breast-fed children. Based on assessment of the components.  |
| <b>Specific Target Organ Toxicity (STOT)</b>                   |  |
| Single Exposure: No end point data for material.               | Not expected to cause organ damage from a single exposure.   |
| Repeated Exposure: No end point data for material.             | Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.                     |

**OTHER INFORMATION**

For the product itself:

**Contains:**

DIETHYLENE GLYCOL (DEG): Orally, DEG is more toxic to humans than animal test data indicate. Probable





Product Name: MOBIL BRAKE FLUID DOT 4

Revision Date: 06 Aug 2021

Page 10 of 11

---

undesirable combustion products. Dispose of empty container as normal refuse.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

|                   |                              |
|-------------------|------------------------------|
| <b>SECTION 14</b> | <b>TRANSPORT INFORMATION</b> |
|-------------------|------------------------------|

**LAND (ADR) :** Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport

|                   |                               |
|-------------------|-------------------------------|
| <b>SECTION 15</b> | <b>REGULATORY INFORMATION</b> |
|-------------------|-------------------------------|

Material is hazardous according to UN GHS Revision 4 Criteria.

**REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

**Listed or exempt from listing/notification on the following chemical inventories :** AIIC, DSL, ENCS, IECSC, KECI, PICCS, TCSI, TSCA

|                   |                          |
|-------------------|--------------------------|
| <b>SECTION 16</b> | <b>OTHER INFORMATION</b> |
|-------------------|--------------------------|

N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H361(D): Suspected of damaging the unborn child; Repro Tox, Cat 2 (Develop)

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

BRENNTAG CHEMICALS (HK) PTE LTD: Section 01: Supplier Mailing Address information was modified.  
Section 01: Company Mailing Address information was modified.



Product Name: MOBIL BRAKE FLUID DOT 4  
Revision Date: 06 Aug 2021  
Page 11 of 11

---

-----  
-----  
The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

-----  
-----  
DGN: 2026805XHK (551435)  
-----  
-----